

# WIRELESS TRANSMITTER

**AT-100**

**FOR FOLKLIFT, PALETTE WEIGHING**



**AD-10F  
WIRELESS DISPLAY**

**CHARGER**

• **Best durability IP67**

- **Standard Li-ion battery**
- **Push-pull connector**
- **Easy battery exchange**
- **Lamp type power switch**

<b>CASE</b>	ABS
<b>EFFECTIVE RESOLUTION</b>	24bits
<b>EXTERNAL RESOLUTION</b>	Up to 100,000 counts
<b>INPUT SENSITIVITY</b>	0.2uV/D
<b>INPUT RANGE</b>	0 ~ 39mV
<b>OUTPUT DATA RATE</b>	4.7 to 200 measurements per second
<b>INDOOR/URBAN RANGE</b>	30m international variant
<b>OUTDOOR RF LINE-OF SIGHT</b>	100m international variant
<b>BATTERY</b>	Rechargeable 18650 Li-ion + PCM
<b>CHARGER</b>	Exclusive battery charger
<b>OPERATING TIME</b>	Approx. 700hr
<b>OPERATING TEMPERATURE</b>	-20°C ~ 60°C
<b>OPERATING HUMIDITY</b>	85% R.H. (no condensation)
<b>ACCESSORY</b>	4 wall fastening lug, charger

